

CIJ/DOD, Consumables, Filter Kits, Spares of Damino®, Videojet®, Image® etc...



- Quality is our top priority
- Quick delivery
- Competetive Pricing
- ☐ ISO certified
- ⇒ 24 x 7 service support







appenen al anale

· BEING INNOVATIVE ·

OREC

SAVINGS GUARANTEED

- ICIPL own modern manufacturing facility and strong R&D enables it to offer you consumables at lower cost than other OEMs • Contracted Procurement of Solvents & Other Contituents directly from Renowened
- manufacturers

ASSURED QUALITY

- All inks undergo rigorous testing in Lab and on dedicated printers to performance and consistency

IMMEDIATE DELIVERY

- Ready Stock for same day supply • Tie up wit Reputed Logistic Companies for All India Deliveries and Exports
- Adeuate stock kept at all times
- Top notch logistic companies are in place to transport goods across India

SOLUTION GUARANTEED

- Capable to provide and to end solutions
- Wide Array of inks available for different Substrates and Applications

GENUINE SPARES & SUPPORT

- Dedicated support service in place, to support all type of Customer



INNOVATIVE CODES (I) PRIVATE LIMITED

Old No 12 New No 22 Nungambakkam High Road Chennai 600034 India Tel 044 4320 4842 E Mail Corporate@icipl.co Website www.icipl.co



BEING INNOVATIVE:

- Strict Quality Control Adherence during manufacturing & Filing
- All fluids are filtered upto 0.25µ using Uitipore GF Filters

- Rainbow varieties of Inks and additives for each different unique
- application capable to produce high volume Inks in large Quantity for all brand Printers
- Quality Spare parts & Filter Kits for Various trands of CIJ & Large Caractor Printers
- 24 x 7 Service support through Wide Network of dedicated Engineers at location nearer to you
- Imported efficient spares for all OEM Brands



A Unique & Economical **Coding Experiance**





- ➡ Seamless Print
- Long lasting spares
- ➡ Long Mileage
- ➡ Offeredable cost
- ➡ Fast, Fair, Fabulous Print Quality

| 333 Small Character Printer

StandardFunctions

- 1. Continuous inkjet printing with Mono print head control & Automatic nozzle cleaning. 2. Single button start & stop; Print Stop function; Password to protect the menus.
- 3. Friendly operation interface; QWERTY key pad with LCD display. 4. Traverse system printing option available in default.
- 5.Logo and graphics printing Option; Julian date printing option available.
- 6.Serial number, shift code, Real time & date printing function available. 7. Time could be offset to hours, 4 clocks could be inserted simultaneously in a message.
- 8.User-defined fonts, capable of printing anything you want
- 9.2 serial numbers could be inserted simultaneously
- 10.Large memory volume of over 1000 messages, WYSIWYG message editing, Locate any point edit.
- 11.Download message or update program by USB disk 12.Print counter & Meter counting option available
- 13. Display the faults and warnings in the screen
- 14.1.5L Capacity of ink & makeup.
- 15.3M conduit
- 16. Pigment, Soft Pigment and Regular model printers available.

PrintCapability

- 1. Print Line: 1-4 lines in 7font, 1-5 lines in 5font With 36 Pixel.
- 2. Message Height: 1-20mm, characters could be bolded 9times.
- 3. 5,7,9.12,16,24,32 type of fonts available, We can print English & Arabic languages.
- 4. Non contact printing 6mm 20mm throw distance.

Power Requirement

1. In put power range 210-230vac(3 amp), Frequency:50 – 60 hz, Power Consumption:60 watts

Consumables

- 1. Unique hydraulic system design with diaphragm operating pump.
- 2. Wide range of inks for various applications MEK, Ethanol&Acetone
- 3. Black, White, Yellow, Green, Blue, Red, Purple, Orange inks are available.

WorkingConditions

1. Working temperature: 5-45 centigrade Working humidity: 10-90 % (non-condensing)

External Connections

- 1. Photocell & encoder
- 2. RS232
- 3. USB
- 4. 24v Alarm
- 5. Positive Air pump

General Accessories

- 1. Photocell Proximity Sensor
- 2. Print head stand
- 3. Printer stand
- 4. Tool kit

- 1. Encoder
- 2. Alarm Beckon
- 3. UPS
- 4. Product counter
- 5. Positive Air kit

Enclosure

SS enclose with IP55

IC ID IS









